

# MP 567

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | 12.5 - 20   |
| <b>UM</b>           | IS STANDARD   |
| <b>CONSTRUCTION</b> | ⊠ BIAS  |
| <b>MACHINERY</b>    | ATTREZZI AGRICOLI / SOLLEVATORE<br>TELESCOPICO / ATTREZZI AGRICOLI /<br>SOLLEVATORE TELESCOPICO /<br>VEICOLO UNIVERSALE |
| <b>VERSIONE</b>     | STANDARD  |
| <b>TIRE TYPE</b>    | TT  |



## DIMENSIONI IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 325  | <b>RIM REC</b> | 11.0           |
| <b>OD (MM)</b>  | 1040 | <b>RIM ALT</b> | 12 SDC         |
| <b>SLR (MM)</b> | 490  | <b>ECE</b>     | E4-54R-0022633 |
| <b>RC (MM)</b>  | 3142 | <b>PR</b>      | 12             |

## LOAD CAPACITY (KG/TIRE)

| <b>KM/H / BAR</b> | <b>3.50</b> |
|-------------------|-------------|
| 90                | 2000        |
| 40                | 2300        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.