


# AGRIMAX RT 600



<b>TIRE SIZE</b>	<b>800/65 R 32</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HARVESTER / SPREADER / TRACTOR / IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	181 A8 ; 178 B

## DIMENSIONS US STANDARD

<b>USA CODE</b>	94039302	<b>RC (IN)</b>	218.8
<b>SW (IN)</b>	30.5	<b>RIM REC</b>	DW 27 B
<b>OD (IN)</b>	71.7	<b>RIM ALT</b>	DH 27 B ; DW 25 B
<b>SLR (IN)</b>	32.4	<b>ECE</b>	E4-106R-001429

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	17	23	29	35	41	46	52	58	64
30	7000	8070	9890	10800	11870	12930	14000	15210	16530	-	-
25	7610	8760	10750	11740	12900	14050	15210	16530	18190	-	-
20	8150	9380	11510	12570	13800	15050	16280	17690	19470	-	-
5 LT	10200	11750	14410	15740	17280	18840	20390	22160	24370	-	-
5 HT	8150	9380	11510	12570	13800	15050	16280	17690	19470	-	-
5 CYC	-	12470	15940	17550	20390	22350	24370	26510	27420	28660	30860

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.