

# SM 55 L5S

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | 12.00 - 24   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> | BIAS   |
| <b>MACHINERY</b>    | UNDERGROUND MINING VEHICLE /<br>LOW PROFILE DUMP TRUCK |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TT   |



## DIMENSIONS IS STANDARD

|                 |      |                 |                           |
|-----------------|------|-----------------|---------------------------|
| <b>OD (MM)</b>  | 1275 | <b>RIM ALT</b>  | 7.33 V; 8; 8.00 V; 8.50 V |
| <b>SLR (MM)</b> | 594  | <b>PR</b>       | 24                        |
| <b>RC (MM)</b>  | 3777 | <b>TRA CODE</b> | L5S                       |
| <b>RIM REC</b>  | 8.5  |                 |                           |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 9.75 |
|------------|------|
| 10         | 7600 |
| 15         | 6610 |
| 25         | 6080 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.