

FLOTATION 648

TIRE SIZE	800/45 - 26.5
UM	IS STANDARD
CONSTRUCTION	⊗ BIAS
MACHINERY	HEUPRESSE / ERNTEMASCHINE / STREUMASCHINE / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	158 A8/155 B
LI/SS FREE ROLLING	170 A8/167 B



ABMESSUNGEN IS STANDARD

SW (MM)	800	RIM REC	AG 28.00
OD (MM)	1393	ECE	E11-106R-004557
SLR (MM)	631	PR	12
RC (MM)	4185		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.50	1.60	1.70
10 FR	7805	8105	8400
20 FR	7025	7295	7560
30 FR	6245	6485	6720
40 FR	5575	5790	6000
50 FR	5020	5210	5450
10 DW	5530	5740	5950
20 DW	4975	5165	5355
30 DW	4425	4590	4760
40 DW	3950	4100	4250
50 DW	3555	3690	3875

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.