

# AGRIMAX FORCE

|                  |                                             |
|------------------|---------------------------------------------|
| <b>TIRE SIZE</b> | <b>IF 900/60 R 38 CFO</b>                   |
| <b>UM</b>        | US STANDARD                                 |
| <b>MACHINERY</b> | HARVESTER / HIGH-POWER TRACTOR<br>/ TRACTOR |
| <b>VERSION</b>   | STANDARD                                    |
| <b>TL/TT</b>     | TL                                          |
| <b>LI/SS</b>     | 184 D                                       |



## DIMENSIONS US STANDARD

|                 |                   |                                      |                 |
|-----------------|-------------------|--------------------------------------|-----------------|
| <b>USA CODE</b> | 94038749          | <b>RIM ALT</b>                       | TW 31 B         |
| <b>SW (IN)</b>  | 36.1              | <b>ECE</b>                           | E11-106R-006493 |
| <b>OD (IN)</b>  | 80.5              | <b>TRA CODE</b>                      | R1W             |
| <b>SLR (IN)</b> | 35.6              | <b>TREAD DEPTH (32<sup>nd</sup>)</b> | 77.49           |
| <b>RC (IN)</b>  | 240.4             | <b>TMPH (TM/H)</b>                   | 0               |
| <b>RIM REC</b>  | DW 30 A ; DW 30 B |                                      |                 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI     | 9     | 12    | 15    | 17    | 20    | 23    | 29    | 35    |
|---------------|-------|-------|-------|-------|-------|-------|-------|-------|
| 45            | 8300  | 9570  | 11010 | 12270 | 13710 | 14980 | 16790 | 18050 |
| FROM 40 TO 25 | 9130  | 10520 | 12100 | 13490 | 15080 | 16470 | 18450 | 19800 |
| 20            | 9490  | 10930 | 12580 | 14020 | 15670 | 17120 | 19180 | 20630 |
| 12            | 9850  | 11350 | 13060 | 14560 | 16280 | 17780 | 19920 | 21430 |
| 5             | 11580 | 13350 | 15370 | 17130 | 19150 | 20910 | 23420 | 25200 |
| UPTO 20 CYC   | 11860 | 13670 | 15730 | 17540 | 19600 | 21410 | 23980 | 25790 |
| UPTO 10 CYC   | 14140 | 16290 | 18750 | 20910 | 23370 | 25520 | 28590 | 30750 |
| UPTO 5 CYC    | 15510 | 17870 | 20570 | 22930 | 25630 | 27990 | 31360 | 33730 |
| 5 HT          | 9490  | 10930 | 12580 | 14020 | 15670 | 17120 | 19180 | 20630 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.