


# AGRIMAX V-FLECTO

<b>TIRE SIZE</b>	<b>VF 600/65 R 28</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HOCHLEISTUNGSTRAKTOR / TRACTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	163 D



## ABMESSUNGEN IS STANDARD

<b>SW (MM)</b>	597	<b>RIM REC</b>	DW 21 B
<b>OD (MM)</b>	1491	<b>RIM ALT</b>	DW 20 B
<b>SLR (MM)</b>	655	<b>ECE</b>	E11-106R-007602
<b>RC (MM)</b>	4453	<b>SRI</b>	700

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.8	2.0
70	2265	2620	2975	3375	3690	4000	4440
<b>FROM 65 TO 40</b>	2490	2880	3270	3705	4050	4390	4875
30	2540	2940	3335	3785	4130	4480	4975
20	2590	2995	3400	3855	4210	4565	5070
10	2740	3170	3595	4080	4455	4830	5365
<b>*UPTO 10 CYC WITH FRONT LOADER</b>	3485	4030	4575	5190	5665	6145	6825
10 HT	2540	2940	3335	3785	4130	4480	4975

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.