

AGRIMAX RT 855

TIRE SIZE	480/80 R 46
UM	US STANDARD
MACHINERY	PULVÉRISATEUR / MACHINE À VENDANGER / TRACTEUR / MOISSONNEUSE / OUTILLAGE AGRICOLE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	164 A8/B



DIMENSIONS US STANDARD

CODE USA	94040537	RC (IN)	231.1
SW (IN)	18.9	RIM REC	DW 16 A ; W 16 A ; DD 16
OD (IN)	76.2	RIM ALT	W 16 L ; DD 16 L ; DW 16 L
SLR (IN)	35.2	ECE	E4-106R-000798

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	17	20	23	29	35	41	46
30	5060	5810	6560	7310	8060	8720	9350	10250	11000
25	5060	5810	6560	7310	8060	8720	9350	10250	11000
20	5420	6230	7020	7830	8630	9340	10030	10970	11790
5 LT	6790	7790	8800	9800	10800	11680	12550	13730	14770
5 HT	5420	6230	7020	7830	8630	9340	10030	10970	11790

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.