


# AGRIMAX SPARGO

TIRE SIZE	VF 380/85 R 34
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRATOR
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS	160 D



## DIMENSÕES US STANDARD

CÓDIGO USA	94075331	RC (IN)	177.7
SW (IN)	15.0	RIM REC	W 13 A
OD (IN)	59.1	RIM ALT	W 12
SLR (IN)	26.7	ECE	E11-106R-009071-01

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	17	20	23	26	29	32	35	38	41	44	46
45	5420	6060	6620	6980	7250	7520	7800	8170	8540	8810	9180
FROM 40 TO 25	5860	6550	7150	7540	7840	8140	8440	8830	9230	9530	9930
20	5970	6680	7290	7700	8000	8300	8610	9010	9420	9730	10120
12	6090	6820	7430	7850	8150	8470	8780	9190	9610	9910	10320
5	6440	7200	7860	8300	8620	8960	9290	9720	10160	10490	10920

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.