

# AW 702

|                           |   |
|---------------------------|---|
| <b>TIRE SIZE</b>          | <b>10.5/65 - 16</b>   |
| <b>UM</b>                 | US STANDARD   |
| <b>CONSTRUCTION</b>       | ⊠ BIAS  |
| <b>MACHINERY</b>          | EMPACADORA DE HENO /<br>MAQUINARIA AGRÍCOLA / REMOLQUE<br>/ COSECHADORA / MAQUINARIA<br>AGRÍCOLA / REMOLQUE |
| <b>VERSIÓN</b>            | STANDARD  |
| <b>TIRE TYPE</b>          | TT  |
| <b>LI/SS FREE ROLLING</b> | 130 A8  |



## DIMENSIONES US STANDARD

|                   |          |                |                 |
|-------------------|----------|----------------|-----------------|
| <b>CÓDIGO USA</b> | 94009275 | <b>RC (IN)</b> | 91.7            |
| <b>SW (IN)</b>    | 10.6     | <b>RIM REC</b> | W 9             |
| <b>OD (IN)</b>    | 29.9     | <b>RIM ALT</b> | W 8; W 8 L      |
| <b>SLR (IN)</b>   | 13.8     | <b>ECE</b>     | E11-106R-003351 |

## LOAD CAPACITY (LBS/TIRE)

| <b>MPH / PSI</b> | <b>77</b> |
|------------------|-----------|
| <b>5 FR</b>      | 5860      |
| <b>15 FR</b>     | 4980      |
| <b>20 FR</b>     | 4700      |
| <b>25 FR</b>     | 4190      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.