

# TR 678

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>600/65 - 34</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> | ❖ BIAS   |
| <b>MACHINERY</b>    | ARBETSFORDON / SLÄPVAGN /<br>ARBETSFORDON / SKOTARE /<br>GRÄVMASKIN / SLÄPVAGN |
| <b>VERSION</b>      | STEEL BELTED   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 164 A2 ; 160 A6  |



## DIMENSIONER IS STANDARD

|                 |      |                 |                 |
|-----------------|------|-----------------|-----------------|
| <b>SW (MM)</b>  | 610  | <b>RIM REC</b>  | DW 20 B         |
| <b>OD (MM)</b>  | 1644 | <b>ECE</b>      | E11-106R-003648 |
| <b>SLR (MM)</b> | 758  | <b>PR</b>       | 14              |
| <b>RC (MM)</b>  | 4916 | <b>TRA CODE</b> | LS2             |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>2.40</b> |
| 30                | 4500        |
| 10                | 5000        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.