


# AGRIMAX RT 657

<b>TIRE SIZE</b>	<b>340/65 R 18</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	VENDIMIADORA / TRACTOR / COSECHADORA
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	113 A8/B



## DIMENSIONES US STANDARD

<b>CÓDIGO USA</b>	94039203	<b>RC (IN)</b>	105.0
<b>SW (IN)</b>	13.5	<b>RIM REC</b>	W 11
<b>OD (IN)</b>	35.4	<b>RIM ALT</b>	W 10 ; W 12
<b>SLR (IN)</b>	15.7	<b>ECE</b>	E4-106R-001816

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
30	1420	1680	1910	2140	2340	2540
25	1420	1680	1910	2140	2340	2540
20	1530	1810	2050	2290	2510	2720
5 LT	1920	2250	2560	2870	3140	3410
5 HT	1530	1810	2050	2290	2510	2720

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.