

# AW 711

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>395/55 R 16.5</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  |
| <b>MACHINERY</b>    | HAY HARVESTER / IMPLEMENT<br>MACHINERY / HARVESTER /<br>IMPLEMENTS |
| <b>VERSION</b>      | STUBBLE RESISTANT  |
| <b>TL/TT</b>        | TL   |
| <b>LI/SS</b>        | 152 A8/B   |



## DIMENSIONS US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94053469 | <b>RC (IN)</b> | 99.1            |
| <b>SW (IN)</b>  | 15.5     | <b>RIM REC</b> | 12              |
| <b>OD (IN)</b>  | 33.0     | <b>ECE</b>     | E11-106R-002997 |
| <b>SLR (IN)</b> | 14.4     |                |                 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12   | 17   | 23   | 29   | 35   | 41   | 46   | 52   | 58    | 73    |
|-----------|------|------|------|------|------|------|------|------|-------|-------|
| 30        | 2350 | 3050 | 3760 | 4310 | 5020 | 5720 | 6110 | 6730 | 7360  | 7830  |
| 25        | 2350 | 3050 | 3760 | 4310 | 5020 | 5720 | 6110 | 6730 | 7360  | 7830  |
| 20        | 2630 | 3430 | 4220 | 4830 | 5620 | 6420 | 6840 | 7550 | 8260  | 8770  |
| 15        | 2800 | 3640 | 4480 | 5130 | 5960 | 6800 | 7270 | 8010 | 8760  | 9310  |
| 10        | 2970 | 3860 | 4740 | 5430 | 6320 | 7210 | 7700 | 8490 | 9280  | 9870  |
| 5         | 3300 | 4280 | 5270 | 6030 | 7020 | 8000 | 8550 | 9420 | 10310 | 10960 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.