


MULTIMAX MP 522



| | |
|---------------------|--|
| TIRE SIZE | 480/80 R 26 IND |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | KOMPAKTLADER / TELESKOPLADER / KOMPAKTLADER / TELESKOPLADER |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 167 A8/B |

ABMESSUNGEN IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 479 | RIM REC | DW 15 L |
| OD (MM) | 1428 | RIM ALT | DW 16 L |
| SLR (MM) | 638 | ECE | E11-106R-008146 |
| RC (MM) | 4287 | SRI | 675 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.6 | 1.8 | 2.0 | 2.2 | 2.4 | 2.6 | 2.8 | 3.0 | 3.2 | 3.4 | 3.6 | 3.8 | 4.0 | 4.2 | 4.4 |
|------------|------|------|------|------|------|------|------|------|------|------|-------|-------|-------|-------|-------|
| 50 | 2575 | 2815 | 3055 | 3295 | 3540 | 3780 | 4020 | 4260 | 4500 | 4740 | 4975 | 5215 | 5450 | - | - |
| 40 | 2575 | 2815 | 3055 | 3295 | 3540 | 3780 | 4020 | 4260 | 4500 | 4740 | 4975 | 5215 | 5450 | - | - |
| 30 | 2790 | 3045 | 3300 | 3550 | 3805 | 4060 | 4315 | 4565 | 4820 | 5075 | 5330 | 5580 | 5835 | - | - |
| 25 | 2890 | 3155 | 3420 | 3680 | 3945 | 4210 | 4475 | 4735 | 5000 | 5265 | 5525 | 5790 | 6050 | - | - |
| 10 CYC. | 3200 | 3555 | 3910 | 4265 | 4620 | 4975 | 5330 | 5685 | 6040 | 6395 | 6750 | 7460 | 8175 | - | - |
| STATIC | 4900 | 5445 | 5990 | 6535 | 7080 | 7625 | 8170 | 8715 | 9260 | 9805 | 10350 | 10895 | 11445 | 11990 | 12535 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.