

# AW 909

|                           |  |
|---------------------------|--|
| <b>TIRE SIZE</b>          | 11.5/80 - 15.3   |
| <b>UM</b>                 | US STANDARD  |
| <b>CONSTRUCTION</b>       | BIAS   |
| <b>MACHINERY</b>          | PRESSE À PAILLE / OUTILLAGE<br>AGRICOLE / REMORQUE /<br>MOISSONNEUSE / OUTILLAGE<br>AGRICOLE |
| <b>VERSION</b>            | STANDARD   |
| <b>TIRE TYPE</b>          | TL   |
| <b>LI/SS FREE ROLLING</b> | 141 A8   |



## DIMENSIONS US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>CODE USA</b> | 94010677 | <b>RC (IN)</b> | 97.4           |
| <b>SW (IN)</b>  | 11.8     | <b>RIM REC</b> | 9.00           |
| <b>OD (IN)</b>  | 33.2     | <b>ECE</b>     | E4-106R-002752 |
| <b>SLR (IN)</b> | 14.6     | <b>PR</b>      | 16             |

## LOAD CAPACITY (LBS/TIRE)

| <b>MPH / PSI</b> | <b>78</b> |
|------------------|-----------|
| 5 FR             | 7950      |
| 15 FR            | 6760      |
| 20 FR            | 6360      |
| 25 FR            | 5680      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.