


AGRIMAX PROCROP

| | |
|---------------------|--|
| TIRE SIZE | VF 270/95 R 38 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | IRRORAZIONE |
| VERSIONE | STEEL BELTED |
| TIRE TYPE | TL |
| LI/SS | 151 D |



DIMENSIONI US STANDARD

| | | | |
|-------------------|----------|----------------|------------------|
| CODICE USA | 94506316 | RC (IN) | 178.8 |
| SW (IN) | 11.0 | RIM REC | W9 |
| OD (IN) | 58.7 | ECE | E11-106R-0010173 |
| SLR (IN) | 27.4 | | |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 14 | 17 | 20 | 23 | 29 | 35 | 41 | 46 | 52 | 58 |
|---------------|------|------|------|------|------|------|------|------|------|------|
| 45 | 3270 | 3680 | 4090 | 4440 | 4920 | 5200 | 5680 | 6170 | 6590 | 6930 |
| FROM 40 TO 25 | 3590 | 4040 | 4500 | 4880 | 5410 | 5710 | 6240 | 6780 | 7240 | 7610 |
| 20 | 3650 | 4130 | 4590 | 4980 | 5520 | 5820 | 6380 | 6920 | 7380 | 7760 |
| 12 | 3730 | 4200 | 4680 | 5080 | 5630 | 5950 | 6500 | 7060 | 7530 | 7920 |
| 5 | 3940 | 4450 | 4940 | 5360 | 5950 | 6290 | 6870 | 7460 | 7960 | 8370 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.