


# AGRIMAX RT 657

	<b>600/65 R 38</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ÜZÜM HASAT MAKINESİ / TRAKTÖR / BIÇERDÖVER
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
	159 D ; 162 A8



## UNDEFINED IS STANDARD

<b>SW (MM)</b>	611	<b>RIM REC</b>	DW 20 B
<b>OD (MM)</b>	1745	<b>RIM ALT</b>	W 18 L
<b>SLR (MM)</b>	790	<b>ECE</b>	E4-106R-000623
<b>RC (MM)</b>	5247	<b>SRI</b>	825

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	2100	2450	2760	3065	3370	3635	4025	4375
50	2210	2575	2895	3220	3540	3815	4230	4595
40	2280	2660	2995	3325	3660	3945	4370	4750
30	2420	2820	3175	3525	3880	4180	4635	5035
10 LT	2820	3285	3695	4110	4520	4870	5400	5865
10 HT	2420	2820	3175	3525	3880	4180	4635	5035

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.