


# RIDEMAX IT 696

<b>TIRE SIZE</b>	<b>360/80 R 20 IND</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	143 D ; 147 A8



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94071074	<b>RC (IN)</b>	127.4
<b>SW (IN)</b>	14.1	<b>RIM REC</b>	11
<b>OD (IN)</b>	42.7	<b>RIM ALT</b>	W 10 ; W 11 ; 12 ; W 12
<b>SLR (IN)</b>	19.2	<b>ECE</b>	E11-106R-007845

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	17	23	29	35	41	46	52	58
40	2890	3490	4160	4630	4810	4990	5470	6010
30	3120	3770	4490	5000	5200	5390	5910	6490
25	3260	3940	4680	5220	5420	5630	6170	6780
20	3460	4190	4980	5560	5780	5990	6570	7210

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.