


AGRIMAX FORCE



TIRE SIZE	IF 710/75 R 42
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	CEIFEIRA / TRATOR DE ALTA POTENCIA / TRATOR
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS	181 D

DIMENSÕES US STANDARD

CÓDIGO USA	94046010	RC (IN)	252.1
SW (IN)	28.2	RIM REC	DW 25 B
OD (IN)	84.0	RIM ALT	DW 23 B
SLR (IN)	38.1	ECE	E11-106R-006490

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	7730	8930	10250	11580	12910	14230	15550	16540
FROM 40 TO 25	8540	9820	11280	12730	14190	15640	17100	18200
20	8880	10210	11720	13240	14750	16260	17780	18910
12	9230	10600	12170	13750	15310	16890	18460	19640
5	10850	12470	14320	16160	18010	19860	21700	23090
UPTO 20 CYC	11100	12760	14650	16540	18440	20330	22220	23640
UPTO 10 CYC	13240	15220	17470	19730	21980	24240	26500	28180
UPTO 5 CYC	14520	16690	19170	21640	24110	26590	29060	30920
5 HT	8880	10210	11720	13240	14750	16260	17780	18910

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.