


AGRIMAX V- FLECTO

TIRE SIZE	VF 600/600 R 34
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRATTORE A ELEVATA POTENZA / TRATTORE
VERSIONE	STANDARD
TIRE TYPE	TL
LI/SS	160 D



DIMENSIONI IS STANDARD

SW (MM)	595	RIM REC	DW 20 B
OD (MM)	1584	RIM ALT	DW 18 L; DW 21 B
SLR (MM)	691	ECE	E11-106R-008773
RC (MM)	4710	SRI	750

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
70	2250	2620	2985	3355	3725	4095
FROM 65 TO 40	2475	2880	3285	3690	4095	4500
30	2520	2935	3350	3760	4175	4590
20	2570	2995	3415	3835	4255	4680
10	2720	3165	3610	4055	4500	4950
*UPTO 10 CYC WITH FRONT LOADER	3465	4030	4595	5165	5730	6300
10HT	2520	2935	3350	3760	4175	4590

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.