


# RIDEMAX IT 696

<b>TIRE SIZE</b>	<b>540/80 R 38 IND</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	172 A8 ; 167 D



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	550	<b>RIM REC</b>	W 18 L
<b>OD (MM)</b>	1829	<b>RIM ALT</b>	W 16 L
<b>SLR (MM)</b>	833	<b>ECE</b>	E11-106R-004077
<b>RC (MM)</b>	5537	<b>SRI</b>	875

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1	1.2	1.4	1.6
65	1075	1250	1425	1600	1775	1950
50	1130	1315	1500	1685	1870	2050
40	1180	1370	1565	1755	1950	2140
30	1235	1440	1640	1845	2045	2245
10 LT	1440	1675	1910	2145	2380	2615
10HT	1235	1440	1640	1845	2045	2245

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.