

# FARM SPECIAL

|                     |                  |
|---------------------|------------------|
|                     | <b>15.5 - 38</b> |
| <b>UM</b>           | IS STANDARD      |
| <b>CONSTRUCTION</b> | ❖ BIAS           |
| <b>MACHINERY</b>    | TRAKTÖR          |
| <b>VERSION</b>      | STANDARD         |
| <b>TIRE TYPE</b>    | TT               |
|                     | 133 A6           |



## UNDEFINED IS STANDARD

|                 |      |                 |                 |
|-----------------|------|-----------------|-----------------|
| <b>SW (MM)</b>  | 394  | <b>RIM REC</b>  | W 14 L          |
| <b>OD (MM)</b>  | 1575 | <b>ECE</b>      | E11-106R-005541 |
| <b>SLR (MM)</b> | 731  | <b>PR</b>       | 8               |
| <b>RC (MM)</b>  | 4813 | <b>TRA CODE</b> | R1              |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>1.80</b> |
| 30                | 2060        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.