


# MULTIMAX MP 527

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>500/70 R 24</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL               |
| <b>MACHINERY</b>    | CARREGADORA COMPACTA /<br>LEVANTADOR TELESCÓPICO /<br>CARREGADORA COMPACTA /<br>LEVANTADOR TELESCÓPICO |
| <b>VERSÃO</b>       | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 164 A8/B   |



## DIMENSÕES US STANDARD

|                   |          |                |                  |
|-------------------|----------|----------------|------------------|
| <b>CÓDIGO USA</b> | 94052233 | <b>RC (IN)</b> | 158.2            |
| <b>SW (IN)</b>    | 19.8     | <b>RIM REC</b> | DW 16 L          |
| <b>OD (IN)</b>    | 51.6     | <b>RIM ALT</b> | DW 15 L; DW 18 L |
| <b>SLR (IN)</b>   | 23.5     | <b>ECE</b>     | E4-106R-002658   |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 23   | 29    | 35    | 41    | 46    | 51    | 58    | 61    | 64    |
|-----------|------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30        | 5290 | 6280  | 7160  | 8160  | 9150  | 9810  | 11020 | -     | -     |
| 25        | 5290 | 6280  | 7160  | 8160  | 9150  | 9810  | 11020 | -     | -     |
| 20        | 5670 | 6720  | 7670  | 8730  | 9800  | 10500 | 11790 | -     | -     |
| 15        | 5870 | 6980  | 7960  | 9060  | 10160 | 10890 | 11230 | -     | -     |
| 5 CYC.    | 6450 | 7940  | 9350  | 10750 | 12230 | 13320 | 15050 | 15870 | 16530 |
| STATIC    | 9890 | 12170 | 14330 | 16480 | 18760 | 20410 | 23070 | 24340 | 25350 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.