


AGRIMAX RT 855

| | |
|---------------------|--------------------------------------------------------------------------------------------------------------|
| TIRE SIZE | 520/85 R 38 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | PULVERIZATOR / MAȘINĂ DE RECOLTAT PODGORII / TRACTOR / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 155 A8/B |



DIMENSIUNI IS STANDARD

| | | | |
|-----------------|------|----------------|-------------------|
| SW (MM) | 516 | RIM REC | DW 16 L |
| OD (MM) | 1849 | RIM ALT | DW 18 L ; DD 16 L |
| SLR (MM) | 813 | ECE | E4-106R-000601 |
| RC (MM) | 5466 | SRI | 875 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 |
|--------------|------|------|------|------|------|------|
| 50 | 2170 | 2560 | 2910 | 3255 | 3565 | 3875 |
| 40 | 2170 | 2560 | 2910 | 3255 | 3565 | 3875 |
| 30 | 2325 | 2740 | 3115 | 3490 | 3820 | 4150 |
| 10 LT | 2910 | 3430 | 3900 | 4365 | 4780 | 5195 |
| 10 HT | 2325 | 2740 | 3115 | 3490 | 3820 | 4150 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.