


# PL 801

<b>TYRE SIZE</b>	<b>7.00 - 15</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	HAY HARVESTER / IMPLEMENTS / ROTOR RAKE / TEDDER / FORKLIFT / HARVESTER / FORKLIFT
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TT



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94007349	<b>RC (IN)</b>	0
<b>SW (IN)</b>	8.1	<b>RIM REC</b>	6.0
<b>OD (IN)</b>	30.5	<b>RIM ALT</b>	5.50 BD ; 5.5
<b>SLR (IN)</b>	0	<b>PR</b>	12

## LOAD CAPACITY (LBS/TYRE)

MPH / PSI	125	130
<b>15 LOAD WHEEL</b>	6245	-
<b>15 STEER WHEEL</b>	5275	-
<b>5 OTHER VEHICLES</b>	5275	-
<b>15 OTHER VEHICLES</b>	3885	-
<b>STATIC SIDE LOADER</b>	-	8520

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.