


BK-LOADER 53

| | |
|---------------------|--|
| TIRE SIZE | 405/70 R 20 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | HJULLASTARE |
| VERSION | ARAMID BELTED |
| TIRE TYPE | TL |
| LI/SS | 155A2/151A4 |



DIMENSIONER US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------------|
| USA CODE | 94054428 | RC (IN) | 131.5 |
| SW (IN) | 16.0 | RIM REC | 13 |
| OD (IN) | 43.2 | RIM ALT | 14; 13 SDC; 12;12 SDC |
| SLR (IN) | 20.1 | | |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 22 | 29 | 36 | 44 | 51 | 58 | 65 | 73 | 80 |
|-----------|------|------|------|------|------|-------|-------|-------|-------|
| 12 | 2670 | 3350 | 3980 | 4610 | 5240 | 5820 | 6400 | 6990 | 7610 |
| 5 | 3030 | 3800 | 4520 | 5240 | 5950 | 6610 | 7270 | 7940 | 8540 |
| STATIC | 4850 | 6060 | 7220 | 8380 | 9530 | 10580 | 11680 | 12680 | 13670 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.