

# AS 504

<b>TIRE SIZE</b>	<b>16.5/85 - 24</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	TELESKOPLADER / FELD-ANHÄNGER / LANDWIRTSCHAFTLICHE GERÄTE / TELESKOPLADER
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	146 A8
<b>LI/SS FREE ROLLING</b>	158 A8



## ABMESSUNGEN US STANDARD

<b>USA-CODE</b>	94019083	<b>RC (IN)</b>	158.0
<b>SW (IN)</b>	16.3	<b>RIM REC</b>	W 13
<b>OD (IN)</b>	52.2	<b>RIM ALT</b>	W 14 L; W 15 L
<b>SLR (IN)</b>	23.0	<b>ECE</b>	E11-106R-005097

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	35
5 FR	13120
15 FR	11150
20 FR	10490
25 FR	9370
5 DW	9260
15 DW	7870
20 DW	7410
25 DW	6610

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.