

TRAC GRADER +



TRAC GRADER +

TRAC GRADER + (G-2) is a bias-ply tyre for graders. It is an excellent choice for the budget-minded customers. The durable casing is designed to last. The self-cleaning tread design shows open lug-to-void-ratio which provides best traction in all conditions. Its "special" version is made of a special cut-and-chip-resistant compound.



	SIZE	TT/TL	TRA CODE	PR	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM							
														
Ø24"	13.00 - 24	TL	G2	16	-	8.00 TG SDC	9.00/1.5 (DC) 10.00/VA SDC	0	340	1280	600	3943	25	STD
	13.00 - 24	TL	G2	14	-	8.00 TG SDC	9.00/1.5 (DC) 10.00/VA SDC	0	340	1280	600	3943	25	STD
	14.00 - 24	TL	G2	16	-	8.00 TG SDC	9.00/1.5 (DC) 10.00/VA SDC	0	364	1348	598	3990	25	STD
	13.00 - 24	TL	G2	12	-	8.00 TG SDC	9.00/1.5 (DC) 10.00/VA SDC	0	340	1280	600	3943	25	SPL

STD: STANDARD, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
			

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 22/09/2026

SIZE	TT/TL	TRA CODE	PR	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
					REC RIM	ALT RIM							
													
14.00 - 24	TL	G2	16	-	8.00 TG SDC	9.00/1.5 (DC) 10.00/VA SDC	0	364	1348	598	3990	25	SPL
13.00 - 24	TL	G2	12	-	8.00 TG SDC	9.00/1.5 (DC) 10.00/VA SDC	0	340	1280	600	3943	25	STD
14.00 - 24	TL	G2	12	-	8.00 TG SDC	9.00/1.5 (DC) 10.00/VA SDC 10.00 WA SDC	0	364	1348	598	3990	25	SPL
14.00 - 24	TL	G2	12	-	8.00 TG SDC	9.00/1.5 (DC) 10.00 VA SDC 10.00 WA SDC	0	364	1348	598	3990	25	STD
14.00 - 24	TT	G2	16	-	8.00 TG SDC	9.00/1.5 (DC) 10.00/VA SDC	0	364	1348	598	3990	25	STD
14.00 - 24	TT	G2	12	-	8.00 TG SDC	9.00/1.5 (DC) 10.00 VA SDC 10.00 WA SDC	0	364	1348	598	3990	25	STD

STD: STANDARD, SPL: SPECIAL



TECHNOLOGIES		PERFORMANCES	
			
			

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 22/09/2026