

BK 6060



BK 6060



BK 6060 is a both field- and road-oriented tire for trailers and backhoe loaders in transport as well as digging and loading applications. This block pattern tire provides an extended tire life-cycle.



SIZE	TT/TL	PR	LI/SS	RIM		O.W. (mm)	OD (mm)	SLR (mm)	RC (mm)	VERSION
				REC RIM	ALT RIM					
										
Ø16"	9.00 - 16	TT	16	-	6.50 H	6.00 G	925	432	2847	IND

IND: INDUSTRIAL

TECHNOLOGIES		PERFORMANCES		Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index
  -		 		

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

CA – 15/07/2026