

# EARTHMAX SR 41

<b>TIRE SIZE</b>	<b>875/65 R 29</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	БУЛЬДОЗЕР / ПОГРУЗЧИК / ШАРНИРНО-СОЧЛЕНЕННЫЙ САМОСВАЛ / НИЗКОПРОФИЛЬНЫЙ САМОСВАЛ
<b>VERSION</b>	CUT RESISTANT COMPOUND
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	203 B ; 214 A2



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94059911	<b>RIM REC</b>	27.00/3.50
<b>OD (IN)</b>	73.4	<b>RIM ALT</b>	27.00/3.0, 28.00/3.5
<b>SLR (IN)</b>	33.0	<b>TRA CODE</b>	E4/L4
<b>RC (IN)</b>	223.6	<b>STAR RATING</b>	★★★

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	58	62	65	69
30	30900	31400	33300	34200
5	40800	43000	45400	46700

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.