

# AW 705

<b>TIRE SIZE</b>	15.0/55 - 17
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	ENFARDADEIRA DE FENO / IMPLEMENTOS AGRÍCOLAS / REBOQUE / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS
<b>VERSÃO</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS FREE ROLLING</b>	134 A8



## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94048335	<b>RC (IN)</b>	101.4
<b>SW (IN)</b>	15.0	<b>RIM REC</b>	13.00
<b>OD (IN)</b>	33.5	<b>RIM ALT</b>	13; W 13
<b>SLR (IN)</b>	15.4	<b>ECE</b>	E11-106R-004250

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>38</b>
5 FR	6550
15 FR	5570
20 FR	5240
25 FR	4670

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.