

# FLOTATION 648

<b>TIRE SIZE</b>	500/50 - 17
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	PRESSA PER BALLE DI FIENO / MIETITREBBIA / SPARGITORE / MIETITREBBIA / ATTREZZI AGRICOLI
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	139 A8/135 B
<b>LI/SS FREE ROLLING</b>	152 A8/148 B



## DIMENSIONI IS STANDARD

<b>SW (MM)</b>	510	<b>RIM REC</b>	16.00
<b>OD (MM)</b>	945	<b>ECE</b>	E4-106R-001886
<b>SLR (MM)</b>	416	<b>PR</b>	16
<b>RC (MM)</b>	2750		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.00	3.10	3.20
10 FR	4790	4880	4970
20 FR	4310	4390	4475
30 FR	3830	3905	3975
40 FR	3420	3485	3550
50 FR	3080	3135	3150
10 DW	3275	3340	3400
20 DW	2950	3005	3060
30 DW	2620	2670	2720
40 DW	2340	2385	2430
50 DW	2105	2145	2180

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.