


AGRIMAX RT 955

	340/85 R 48
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ILAÇLAMA / ÜZÜM HASAT MAKİNESİ / BIÇERDÖVER / UYGULAMALI MAKİNE
VERSION	STANDARD
TIRE TYPE	TL
	151 D ; 154 A8



UNDEFINED IS STANDARD

SW (MM)	353	RIM REC	W 12
OD (MM)	1797	RIM ALT	W 11
SLR (MM)	855	ECE	E11-106R-005765
RC (MM)	5572	SRI	875

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4
65	1485	1660	1865	2040	2245	2385	2625	2830	3005	3175	3450
50	1560	1740	1960	2140	2360	2505	2755	2975	3155	3335	3625
40	1615	1800	2025	2215	2440	2590	2850	3075	3265	3450	370
30	1710	1910	2145	2345	2585	2740	3020	3260	3455	3655	3970
10	2230	2485	2975	3055	3365	3575	3935	4245	4505	4765	5175

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.