


# AGRIMAX RT 765

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>320/70 R 24</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | SPRAYER / TRACTOR / VINEYARD<br>HARVESTER / HARVESTER /<br>IMPLEMENTS                    |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 116 D  |



## DIMENSIONS US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94063031 | <b>RC (IN)</b> | 127.8           |
| <b>SW (IN)</b>  | 12.6     | <b>RIM REC</b> | W 10            |
| <b>OD (IN)</b>  | 43.1     | <b>RIM ALT</b> | W 9; W 11       |
| <b>SLR (IN)</b> | 19.8     | <b>ECE</b>     | E11-106R-005827 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9    | 12   | 15   | 17   | 20   | 23   |
|-----------|------|------|------|------|------|------|
| 40        | 1520 | 1760 | 2020 | 2260 | 2510 | 2760 |
| 30        | 1600 | 1860 | 2120 | 2380 | 2650 | 2900 |
| 25        | 1660 | 1940 | 2220 | 2480 | 2760 | 3020 |
| 20        | 1750 | 2040 | 2330 | 2610 | 2900 | 3170 |
| 5 LT      | 2040 | 2370 | 2700 | 3030 | 3360 | 3690 |
| 5 HT      | 1750 | 2040 | 2330 | 2610 | 2900 | 3170 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.