

FARM 2000

| | |
|---------------------------|--------------------|
| TIRE SIZE | 250/80 - 16 |
| UM | IS STANDARD |
| CONSTRUCTION | ⊠ BIAS |
| MACHINERY | TRACTOR |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 113 A8 |
| LI/SS FREE ROLLING | 125 A8 |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 240 | RIM REC | W 8 |
| OD (MM) | 820 | RIM ALT | W 7; W 9; W 8 L |
| SLR (MM) | 369 | ECE | E11-106R-003518 |
| RC (MM) | 2429 | SRI | 390 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 2.80 |
|-------------------|-------------|
| 10 FR | 2310 |
| 25 FR | 1965 |
| 30 FR | 1850 |
| 40 FR | 1650 |
| 10 DW | 1610 |
| 25 DW | 1370 |
| 30 DW | 1290 |
| 40 DW | 1150 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.