

AGRIMAX RT 600

| | |
|---------------------|--|
| TIRE SIZE | 900/60 R 32 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | КОМБАЙН / РАЗБРАСЫВАТЕЛЬ / ТРАКТОР-ТЯГАЧ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 181 A8 ; 178 B |



РАЗМЕРЫ IS STANDARD

| | | | |
|-----------------|------|----------------|------------------|
| SW (MM) | 896 | RIM REC | DW 27 B |
| OD (MM) | 1893 | RIM ALT | DW 28 B; DW 30 B |
| SLR (MM) | 841 | ECE | E11-106R-005768 |
| RC (MM) | 5697 | SRI | 900 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.4 | 3.8 |
|------------|------|------|------|------|------|-------|-------|-------|-------|-------|-------|
| 50 | 3375 | 3825 | 4350 | 4800 | 5325 | 5925 | 6375 | 6975 | 7500 | - | - |
| 40 | 3715 | 4210 | 4785 | 5280 | 5860 | 6520 | 7015 | 7675 | 8250 | - | - |
| 30 | 3975 | 4505 | 5125 | 5655 | 6270 | 6980 | 7510 | 8215 | 8830 | - | - |
| 10 LT | 4975 | 5640 | 6415 | 7080 | 7850 | 8735 | 9400 | 10285 | 11055 | - | - |
| 10 HT | 3975 | 4505 | 5125 | 5655 | 6270 | 6980 | 7510 | 8215 | 8830 | - | - |
| 10 CYC. | - | 6765 | 7690 | 8485 | 9415 | 10475 | 11270 | 12330 | 13255 | 13465 | 14025 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.