


# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>250/85 R 24</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	FELDSPRITZE / TRAUBENERNTEMASCHINE / TRACTOR / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	109 A8/B



## ABMESSUNGEN IS STANDARD

<b>SW (MM)</b>	251	<b>RIM REC</b>	W 8
<b>OD (MM)</b>	1036	<b>RIM ALT</b>	W 7 ; W 9
<b>SLR (MM)</b>	475	<b>ECE</b>	E4-106R-000638
<b>RC (MM)</b>	3104	<b>SRI</b>	500

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
<b>50</b>	570	660	755	845	940	1030
<b>40</b>	570	660	755	845	940	1030
<b>30</b>	610	710	810	910	1010	1105
<b>10 LT</b>	765	890	1015	1140	1265	1385
<b>10 HT</b>	610	710	810	910	1010	1105

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.