


# AGRIMAX ELOS

<b>TYRE SIZE</b>	<b>520/85 R 42</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	167 A8/B



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	516	<b>RIM REC</b>	DW 16 L
<b>OD (MM)</b>	1988	<b>RIM ALT</b>	DD 18 L ; DW 18 L
<b>SLR (MM)</b>	920	<b>ECE</b>	E11-106R-0010146
<b>RC (MM)</b>	6095	<b>SRI</b>	925

## LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2	2.4	2.8	3.2
<b>50</b>	2130	2510	2890	3220	3600	3925	4310	4745	5125	5450
<b>40</b>	2130	2510	2890	3220	3600	3925	4310	4745	5125	5450
<b>30</b>	2280	2685	3095	3445	3855	4205	4610	5080	5485	5835
<b>10 LT</b>	2850	3365	3875	4310	4825	5260	5775	6360	6870	7305
<b>10 HT</b>	2280	2685	3095	3445	3855	4205	4610	5080	5485	5835

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.