


# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>420/85 R 30</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PULVERIZATOR / MAȘINĂ DE RECOLTAT PODGORII / TRACTOR / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	140 A8/B



## DIMENSIUNI US STANDARD

<b>USA CODE</b>	94021734	<b>RC (IN)</b>	174.1
<b>SW (IN)</b>	17.2	<b>RIM REC</b>	W 15 L
<b>OD (IN)</b>	58.1	<b>RIM ALT</b>	W 13 ; W 14 L
<b>SLR (IN)</b>	26.0	<b>ECE</b>	E4-106R-000654

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
<b>30</b>	3030	3530	4020	4520	5020	5500
<b>25</b>	3030	3530	4020	4520	5020	5500
<b>20</b>	3250	3780	4310	4840	5370	5900
<b>5 LT</b>	4070	4730	5400	6060	6720	7390
<b>5 HT</b>	3250	3780	4310	4840	5370	5900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.