

AGRIMAX RT 955

| | |
|---------------------|---|
| TIRE SIZE | 300/95 R 52 |
| UM | IS STANDARD |
| CONSTRUCTION | |
| MACHINERY | SPRAYER / VINEYARD HARVESTER / HARVESTER / IMPLEMENTS |
| VERSION | STANDARD |
| TL/TT | TL |
| LI/SS | 151 A8/B |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------------------|
| SW (MM) | 295 | RIM REC | W 9 |
| OD (MM) | 1891 | RIM ALT | W 10 ; W 11 ; DW 10 ; DW 11 |
| SLR (MM) | 889 | ECE | E4-106R-001484 |
| RC (MM) | 5774 | SRI | 900 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.8 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 | 4.4 |
|------------|------|------|------|------|------|------|------|------|------|------|
| 50 | 1350 | 1760 | 2140 | 2350 | 2485 | 2730 | 2970 | 3210 | 3450 | - |
| 40 | 1350 | 1760 | 2140 | 2350 | 2485 | 2730 | 2970 | 3210 | 3450 | - |
| 30 | 1445 | 1885 | 2295 | 2515 | 2665 | 2920 | 3180 | 3440 | 3695 | - |
| 10 | 1605 | 2020 | 2485 | 2950 | 3420 | 3520 | 3935 | 4350 | 4765 | 5175 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.