


AGRIMAX V- FLECTO

TIRE SIZE	VF 340/85 R 28
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ТРАКТОР ВЫСОКОЙ МОЩНОСТИ / ТРАКТОР-ТЯГАЧ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	139 D



РАЗМЕРЫ IS STANDARD

SW (MM)	355	RIM REC	W 12
OD (MM)	1290	RIM ALT	W 11
SLR (MM)	571	ECE	E11-106R-0010342
RC (MM)	3833	SRI	625

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1	1.2	1.4	1.6
70	1215	1410	1610	1810	2010	2210
FROM 65 TO 40	1335	1555	1770	1990	2210	2430
30	1360	1580	1805	2025	2250	2475
20	1385	1615	1840	2070	2295	2525
10	1600	2135	2670	3200	2425	2670
*UPTO 10 CYC WITH FRONT LOADER	1870	2175	2480	2785	3090	3400
10HT	1360	1580	1805	2025	2250	2475

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.