

FL 630 SUPER

TIRE SIZE	560/60 R 22.5
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	РАЗБРАСЫВАТЕЛЬ / АВТОЦИСТЕРНА / ПРИЦЕП / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	161 D



РАЗМЕРЫ IS STANDARD

SW (MM)	543	RIM REC	AG 16.00
OD (MM)	1244	RIM ALT	17.00; 20.00
SLR (MM)	549	ECE	E4-106R-000794
RC (MM)	3785	SRI	600

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1360	1575	1785	2125	2510	2870	3190	3570	3910	4250
65	1480	1715	1945	2315	2730	3125	3470	3885	4255	4625
50	1795	2075	2355	2800	3305	3780	4200	4705	5155	5600
40	2015	2330	2645	3145	3715	4250	4720	5285	5790	6290
25	2340	2710	3075	3655	4315	4935	5485	6145	6730	7310
10	2665	3085	3500	4165	5915	5620	6245	6995	7660	8325

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.