


EARTHMAX SR 41

| | |
|---------------------|--|
| TIRE SIZE | 29.5 R 25 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | CAMION À BENNE BASCULANTE / BULLDOZER / CHARGEUR / TOMBREAU ARTICULÉ |
| VERSION | CUT RESISTANT COMPOUND |
| TIRE TYPE | TL |
| LI/SS | 200 B ; 208 A2 |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|--------------------|-----------|
| CODE USA | 94039852 | RIM REC | 25.00/3.5 |
| OD (IN) | 73.3 | TRA CODE | E4/L4 |
| SLR (IN) | 32.7 | STAR RATING | ★★/★ |
| RC (IN) | 216.9 | | |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 58 | 62 | 65 | 69 | 73 | 76 |
|-----------|-------|-------|-------|-------|-------|-------|
| 30 | 25400 | 26000 | 27600 | 28300 | 30000 | 30900 |
| 5 | 34200 | 35300 | 37500 | 38600 | 39700 | -- |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.