

FLOTATION 648

TIRE SIZE	500/50 - 22.5
UM	US STANDARD
CONSTRUCTION	⊗ BIAS
MACHINERY	BALPRESS / SKÖRDEMASKIN / SPRIDARE / SKÖRDEMASKIN / ARBETSFORDON
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	146 A8/142 B
LI/SS FREE ROLLING	158 A8/155 B



DIMENSIONER US STANDARD

USA CODE	94006335	RC (IN)	126.0
SW (IN)	19.7	RIM REC	AG 16.00
OD (IN)	42.1	ECE	E4-106R-001560
SLR (IN)	18.7	PR	16

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	38	41	44
5 FR	12070	12590	13120
10 FR	10860	11330	11810
20 FR	9660	10070	10490
25 FR	8620	8990	9370
30 FR	7760	8090	8540
5 DW	8520	8880	9260
10 DW	7670	8000	8330
20 DW	6810	7110	7410
25 DW	6080	6350	6610
30 DW	5480	5710	5840

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.