


# RIDEMAX FL 699

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | 525/65 R 20.5  |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | AUTOBOTTE / RIMORCHIO / ATTREZZI<br>AGRICOLI   |
| <b>VERSIONE</b>     | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 173 F  |



## DIMENSIONI IS STANDARD

|                 |       |            |                 |
|-----------------|-------|------------|-----------------|
| <b>OD (MM)</b>  | 1200  | <b>ECE</b> | E11-54R-0018927 |
| <b>SLR (MM)</b> | 544   | <b>PR</b>  | 20              |
| <b>RC (MM)</b>  | 3678  |            |                 |
| <b>RIM REC</b>  | 16.00 |            |                 |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>8.00</b> |
| 80                | 6500        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.