

## TR 135

|                     |                                                                                        |
|---------------------|----------------------------------------------------------------------------------------|
| <b>TIRE SIZE</b>    | <b>14.9 - 24</b>                                                                       |
| <b>UM</b>           | US STANDARD                                                                            |
| <b>CONSTRUCTION</b> |  BIAS |
| <b>MACHINERY</b>    | TRACTEUR / REMORQUE                                                                    |
| <b>VERSION</b>      | STANDARD                                                                               |
| <b>TIRE TYPE</b>    | TL                                                                                     |
| <b>LI/SS</b>        | 124 A8                                                                                 |



### DIMENSIONS US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>CODE USA</b> | 94003464 | <b>RC (IN)</b> | 151.1          |
| <b>SW (IN)</b>  | 14.9     | <b>RIM REC</b> | W 13           |
| <b>OD (IN)</b>  | 49.8     | <b>RIM ALT</b> | W 12 ; W 11    |
| <b>SLR (IN)</b> | 22.7     | <b>ECE</b>     | E4-106R-002029 |

### LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>26</b> |
| 25               | 3520      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.