


AGRIMAX SPARGO

| | |
|---------------------|--|
| TIRE SIZE | VF 380/90 R 50 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 175 D |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94065264 | RC (IN) | 234.3 |
| SW (IN) | 15.4 | RIM REC | W13 B |
| OD (IN) | 76.8 | RIM ALT | W12 B |
| SLR (IN) | 35.2 | ECE | E11-106R-006400 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 17 | 20 | 23 | 26 | 29 | 32 | 35 | 38 | 41 | 44 | 47 | 49 | 52 | 55 | 58 | 51 | 64 |
|---------------|------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 45 | 6640 | 7470 | 8160 | 8580 | 8990 | 9260 | 9540 | 10100 | 10510 | 10930 | 11350 | 11750 | 12030 | 12450 | 12720 | 13280 | 13840 |
| FROM 40 TO 25 | 7300 | 8220 | 8980 | 9430 | 9890 | 10190 | 10500 | 11100 | 11560 | 12020 | 12470 | 12930 | 13230 | 13690 | 13990 | 14600 | 15220 |
| 20 | 7450 | 8370 | 9150 | 9620 | 10080 | 10390 | 10700 | 11330 | 11790 | 12250 | 12710 | 13180 | 13500 | 13960 | 14270 | 14890 | 15510 |
| 12 | 7590 | 8540 | 9330 | 9800 | 10280 | 10600 | 10920 | 11550 | 12020 | 12490 | 12970 | 13440 | 13760 | 14240 | 14550 | 15180 | 15820 |
| 5 | 8030 | 9030 | 9870 | 10380 | 10870 | 11210 | 11550 | 12220 | 12710 | 13220 | 13720 | 14220 | 14550 | 15060 | 15390 | 16060 | 16740 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.