

TR 135



TR 135



TR 135 is best suitable for tractors in soil tillage applications. Its reinforced casing and the special cut-and-chip resistance compound provide an extended tire life-cycle. Traction, self-cleaning proprieties and load capacity are key features which make the TR 135 tire the ideal partner even on the most difficult ground conditions.



	SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
			REC RIM	ALT RIM						
										
Ø16"	12.4 - 16	97 A6	W 11	W 9 9 W 10	326	960	431	2852	-	STD
	12.4 - 16	111 A6	W 11	W 9 9 W 10	326	960	431	2852	-	STD
Ø20"	9.5 - 20	107 A6	W 8	W 7	240	955	454	2888	-	HD
	8.00 - 20	111 A6	5.50 F	-	225	965	448	2837	-	STD
	12.4 - 20	116 A6	W 11	W 9 9 W 10 11	325	1075	500	3160	-	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A6	168 kg	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference, SRI index

SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
		REC RIM	ALT RIM						
									
11.2 - 20	111 A6	W 10	W 9 9	292	1020	466	3077	-	STD
10.00 - 20	152 A2	7.5	-	280	1075	495	3160	-	STD
9.5 - 20	107 A6	W 8	W 7	240	955	454	2888	-	STD
8.00 - 20	105 A6	5.50 F	-	225	965	448	2837	-	STD
9.5 - 20	102 A6	W 8	W 7	240	955	444	2881	-	STD
12.4 - 20	116 A6	W 11	W 9 9 W 10 11	325	1075	500	3160	-	HD
Ø24"	12.4 - 24	128 A6	W 11 W 9 W 10	315	1160	543	3573	550	STD
	13.6 - 24	123 A6	W 12 W 11	355	1220	562	3698	-	STD
	8.3 - 24	100 A6	W 7 W 6	211	995	469	2985	-	STD
	13.6 - 24	123 A6	W 12 W 11	355	1220	562	3698	-	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A6	168 kg	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
		REC RIM	ALT RIM						
									
12.4 - 24	121 A6	W 11	W 9 W 10	315	1160	531	3477	550	HD
11.2 - 24	116 A6	W 10	W 9	284	1105	507	3303	525	HD
14.9 - 24	135 A6	W 13	W 12 W 11	378	1265	576	3837	600	STD
12.4 - 24	125 A6	W 11	W 9 W 10	315	1160	543	3573	550	STD
8.3 - 24	105 A6	W 7	W 6	211	995	469	2985	-	HD
11.2 - 24	120 A6	W 10	W 9	284	1105	517	3399	525	HD
13.6 - 24	130 A6	W 12	W 11	355	1220	562	3698	-	HD
16.9 - 24	136 A6	W 15 L	W 14 L	429	1335	613	3925	-	STD
14.9 - 24	135 A6	W 13	W 12 W 11	378	1265	576	3837	600	STD
12.4 - 24	121 A6	W 11	W 9 W 10	315	1160	543	3573	550	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A6	168 kg	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference, SRI index

SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
		REC RIM	ALT RIM						
									
14.9 - 24	132 A6	W 13	W 11 W 12	378	1265	576	3837	600	HD
11.2 - 24	110 A6	W 10	W 9	284	1105	517	3399	525	STD
16.9 - 24	140 A6	W 15 L	W 14 L	429	1335	601	4075	-	HD
11.2 - 24	120 A6	W 10	W 9	284	1105	517	3399	525	HD
9.5 - 24	116 A6	W 8	W 7	241	1060	502	3234	-	STD
14.9 - 24	128 A6	W 13	W 12 W 11	378	1265	576	3837	600	STD
14.9 - 24	128 A6	W 13	W 12 W 11	378	1265	570	3769	600	HD
8.3 - 24	105 A6	W 7	W 6	211	995	475	3076	-	STD
16.9 - 24	133 A6	W 15 L	W 14 L	429	1335	613	3925	-	HD
14.9 - 24	135 A6	W 13	W 12 W 11	378	1265	576	3837	600	HD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A6	168 kg	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
		REC RIM	ALT RIM						
									
11.2 - 24	116 A6	W 10	W 9	284	1105	517	3399	25	STD
12.4 - 24	128 A6	W 11	W 9 W 10	315	1160	543	3573	550	SPL
14.9 - 24	128 A6	W 13	W 12 W 11	378	1265	576	3837	600	STD
14.9 - 24	128 A6	W 13	W 11 W 12	378	1265	570	3769	600	HD
11.2 - 24	116 A6	W 10	W 9	284	1105	517	3399	525	STD
13.6 - 24	123 A6	W 12	W 11	355	1220	562	3698	-	HD
12.4 - 24	121 A6	W 11	W 9 W 10	315	1160	543	3523	550	STD
16.9 - 24	133 A6	W 15 L	W 14 L	429	1335	613	3925	-	STD
9.5 - 24	116 A6	W 8	W 7	241	1060	502	3234	-	HD
13.6 - 24	130 A6	W 12	W 11	355	1220	562	3698	-	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A6	168 kg	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
		REC RIM	ALT RIM						
									
16.9 - 24	136 A6	W 15 L	W 14 L	429	1335	613	3925	-	STD
9.5 - 24	112 A6	W 8	W 7	241	1060	502	3234	-	HD
9.5 - 24	112 A6	W 8	W 7	241	1060	502	3234	-	STD
8.3 - 24	111 A6	W 7	W 6	211	995	469	2985	-	HD
16.9 - 24	133 A6	W 15 L	W 14 L	429	1335	613	3925	-	STD
12.4 - 24	115 A6	W 11	W 9 W 10	315	1160	543	3573	550	STD
12.4 - 24	121 A6	W 11	W 9 W 10	315	1160	531	3477	550	HD
9.5 - 24	106 A6	W 8	W 7	241	1060	502	3234	-	STD
12.4 - 24	128 A6	W 11	W 9 W 10	315	1160	543	3573	550	STD
Ø26"	14.9 - 26	129 A6	W 13 W 11 W 12	375	1315	599	3947	-	HD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A6	168 kg	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
		REC RIM	ALT RIM						
									
23.1 - 26	153 A6	DW 20 B DW 20 A	-	587	1585	700	4615	750	STD
23.1 - 26	161 A6	DW 20 B DW 20 A	-	587	1585	700	4615	750	DB
23.1 - 26	159 A6	DW 20 B DW 20 A	-	587	1585	700	4615	750	DB
23.1 - 26	153 A6	DW 20 B DW 20 A	-	587	1585	700	4615	750	STD
16.9 - 26	137 A6	W 15 L	W 14 L	430	1380	625	4183	-	STD
23.1 - 26	153 A6	DW 20 B DW 20 A	-	587	1585	700	4615	750	DB
16.9 - 26	140 A6	W 15 L	W 14 L	430	1380	625	4183	-	STD
23.1 - 26	159 A6	DW 20 B DW 20 A	-	587	1585	700	4615	750	STD
16.9 - 26	137 A6	W 15 L	W 14 L	430	1380	625	4183	-	STD
23.1 - 26	159 A6	DW 20 B DW 20 A	-	587	1585	700	4615	750	HD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A6	168 kg	

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference, SRI index

SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
		REC RIM	ALT RIM						
									
23.1 - 26	159 A6	DW 20 B DW 20 A	-	587	1585	700	4615	750	STD
14.9 - 26	136 A6	W 13	W 11 W 12	375	1315	599	3947	-	STD
23.1 - 26	156 A6	DW 20 B DW 20 A	-	587	1585	700	4615	750	STD
14.9 - 26	129 A6	W 13	W 11 W 12	375	1315	599	3947	-	STD
23.1 - 26	159 A6	DW 20 B DW 20 A	-	587	1585	700	4615	750	DB HD
23.1 - 26	153 A6	DW 20 B DW 20 A	-	587	1585	700	4615	750	DB
Ø28"	14.9 - 28	125 A6	W 13 W 11 W 12	378	1365	634	4170	650	STD
	11.2 - 28	118 A6	W 10 W 9	284	1205	565	3543	575	STD
	9.5 - 28	108 A6	W 8 W 7	235	1155	548	3557	-	STD
	13.6 - 28	134 A6	W 12 W 11	345	1310	606	3908	625	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A6	168 kg	

Permissible tolerances: O.O. 2%—S.W. 2%—RC 2.5%—LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
		REC RIM	ALT RIM						
									
8.3 - 28	108 A6	W 7	W 6	213	1104	519	3347	-	STD
14.9 - 28	137 A6	W 13	W 11 W 12	378	1365	634	4170	650	STD
18.4 - 28	147 A6	W 16 L	W 15 L	467	1501	691	4413	-	STD
14.9 - 28	139 A6	W 13	W 11 W 12	378	1365	634	4170	650	STD
12.4 - 28	131 A6	W 11	W 9 W 10	325	1260	584	3876	600	STD
14.9 - 28 (28)	130 A6	W 13	W 11 W 12	378	1365	634	4170	650	STD
12.4 - 28	123 A6	W 11	W 9 W 10	325	1260	584	3876	600	HD
14.9 - 28	137 A6	W 13	W 11 W 12	378	1365	634	4170	650	HD
11.2 - 28	122 A6	W 10	W 9	284	1205	565	3543	575	STD
9.5 - 28	114 A6	W 8	W 7	235	1155	548	3557	-	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A6	168 kg	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
		REC RIM	ALT RIM						
									
13.6 - 28	137 A6	W 12	W 11	345	1310	606	3908	625	STD
14.9 - 28	130 A6	W 13	W 11 W 12	378	1365	634	4170	650	HD
8.3 - 28	103 A6	W 7	W 6	213	1104	519	3347	-	STD
14.9 - 28	130 A6	W 13	W 11 W 12	378	1365	634	4170	650	STD
13.6 - 28	125 A6	W 12	W 11	345	1310	606	3908	625	STD
13.6 - 28	125 A6	W 12	W 11	345	1310	607	4023	625	HD
12.4 - 28	123 A6	W 11	W 9 W 10	325	1260	584	3876	600	STD
12.4 - 28	117 A6	W 11	W 9 W 10	325	1260	584	3876	600	STD
12.4 - 28	127 A6	W 11	W 9 W 10	325	1260	584	3876	600	STD
11.2 - 28	118 A6	W 10	W 9	284	1205	565	3543	575	HD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A6	168 kg	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference, SRI index

	SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
			REC RIM	ALT RIM						
										
	18.4 - 28	138 A6	W 16 L	W 15 L	467	1501	691	4413	-	STD
Ø30"	18.4 - 30	149 A6	W 16 L	W 15 L	460	1545	697	4712	725	STD
	23.1 - 30	164 A6	DW 20 B DW 20 A	-	600	1700	773	5217	-	DB
	18.4 - 30	154 A6	W 16 L	W 15 L	460	1545	697	4712	725	STD
	18.4 - 30	151 A6	W 16 L	W 15 L	460	1545	697	4712	725	STD
	9.5 - 30	109 A6	W 8	W 7	241	1200	567	3528	-	STD
	16.9 - 30	139 A6	W 15 L	W 14 L	429	1485	678	4535	700	STD
	23.1 - 30	155 A6	DW 20 B DW 20 A	-	600	1700	798	5046	-	STD
	16.9 - 30 (14 - 30)	146 A6	W 15 L	W 14 L	429	1485	678	4535	700	STD
	23.1 - 30	155 A6	DW 20 B DW 20 A	-	600	1700	773	5217	-	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A6	168 kg	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
		REC RIM	ALT RIM						
									
9.5 - 30	115 A6	W 8	W 7	241	1200	567	3528	-	STD
18.4 - 30	145 A6	W 16 L	W 15 L	460	1545	697	4712	725	STD
14.9 - 30	131 A6	W 13	W 11 W 12	378	1415	659	4316	675	STD
18.4 - 30	145 A6	W 16 L	W 15 L	460	1545	697	4712	725	HD
23.1 - 30	146 A6	DW 20 B DW 20 A	-	600	1700	773	5217	-	STD
18.4 - 30	149 A6	W 16 L	W 15 L	460	1545	697	4712	725	STD
18.4 - 30	139 A6	W 16 L	W 15 L	460	1545	697	4712	725	STD
23.1 - 30	146 A6	DW 20 B DW 20 A	-	600	1700	773	5217	-	STD
18.4 - 30	149 A6	W 16 L	W 15 L	460	1545	697	4712	725	HD
7.2 - 30	95 A6	W 6	-	185	1095	523	3219	-	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A6	168 kg	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
		REC RIM	ALT RIM						
									
18.4 - 30	145 A6	W 16 L	W 15 L	460	1545	697	4712	725	HD
16.9 - 30	137 A6	W 15 L	W 14 L	429	1485	678	4535	700	STD
15 - 30 (18.4 - 30)	151 A6	W 16 L	W 15 L	460	1545	714	4542	725	STD
16.9 - 30 (14 - 30)	149 A6	W 15 L	W 14 L	429	1485	678	4535	700	STD
15 - 30 (18.4 - 30)	149 A6	W 16 L	W 15 L	460	1545	714	4542	725	STD
18.4 - 30	139 A6	W 16 L	W 15 L	460	1545	697	4712	725	HD
23.1 - 30	155 A6	DW 20 B DW 20 A	-	600	1700	773	5217	-	DB
23.1 - 30	164 A6	DW 20 B DW 20 A	-	600	1700	773	5217	-	DB
Ø32"	12.4 - 32	124 A6	W 11 W 9 W 10	325	1360	639	3998	650	STD
	12.4 - 32	124 A6	W 11 W 9 W 10	325	1360	639	3998	650	HD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
			
Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index			

SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
		REC RIM	ALT RIM						
									
12.4 - 32	128 A6	W 11	W 9 W 10	325	1360	639	3998	650	HD
8.3 - 32	111 A6	W 7	W 6	211	1195	572	3585	-	STD
8.3 - 32	105 A6	W 7	W 6	211	1195	572	3585	-	STD
9.5 - 32	110 A6	W 8	W 7	235	1255	594	3686	-	STD
12.4 - 32	119 A6	W 11	W 9 W 10	325	1360	639	3998	650	STD
11.2 - 32	120 A6	W 10	W 9	287	1310	615	4007	-	HD
16.9 - 34	142 A6	W 15 L	W 14 L	429	1585	728	4794	750	HD
18.4 - 34	151 A6	W 16 L	W 15 L	467	1650	751	5009	775	STD
18.4 - 34	146 A6	W 16 L	W 15 L	467	1650	751	5009	775	HD
23.1 - 34	153 A6	DW 20 B DW 20 A	-	585	1810	834	5321	-	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A6	168 kg	

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
		REC RIM	ALT RIM						
									
18.4 - 34	154 A6	W 16 L	W 15 L	467	1650	751	5009	775	HD
18.4 - 34	154 A6	W 16 L	W 15 L	467	1650	751	5009	775	STD
16.9 - 34	144 A6	W 15 L	W 14 L	429	1585	728	4794	750	HD
16.9 - 34	144 A6	W 15 L	W 14 L	429	1585	728	4794	750	STD
16.9 - 34	142 A6	W 15 L	W 14 L	429	1585	728	4794	750	STD
18.4 - 34	142 A6	W 16 L	W 15 L	467	1650	751	5009	775	STD
16.9 - 34	139 A6	W 15 L	W 14 L	429	1585	728	4794	750	HD
16.9 - 34	139 A6	W 15 L	W 14 L	429	1585	728	4794	750	STD
18.4 - 34	151 A6	W 16 L	W 15 L	467	1650	751	5009	775	HD SPL
18.4 - 34	137 A6	W 16 L	W 15 L	467	1650	751	5009	775	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
 R1  A6	 168 kg		Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
		REC RIM	ALT RIM						
									
18.4 - 34	151 A6	W 16 L	W 15 L	467	1650	751	5009	775	HD
23.1 - 34	153 A6	DW 20 B DW 20 A	-	585	1810	834	5321	-	STD
18.4 - 34	142 A6	W 16 L	W 15 L	467	1650	732	4860	775	HD
16.9 - 34	142 A6	W 15 L	W 14 L	429	1585	728	4794	750	HD
18.4 - 34	146 A6	W 16 L	W 15 L	467	1650	751	5009	775	STD
Ø36"	13.6 - 36	W 12	W 11	345	1515	713	4687	725	STD
	12.4 - 36	W 11	W 9 W 10	325	1465	696	4546	700	HD
	12.4 - 36	W 11	W 9 W 10	325	1465	696	4546	700	HD
	13.6 - 36	W 12	W 11	345	1515	713	4687	725	HD
	12.4 - 36	W 11	W 9 W 10	325	1465	696	4546	700	HD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A6	168 kg	

Permissible tolerances: 0.0. 2%—S.W. 2%—RC 2.5%—LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
		REC RIM	ALT RIM						
									
12.4 - 36	131 A6	W 11	W 9 W 10	325	1465	696	4546	700	STD
12.4 - 36	135 A6	W 11	W 9 W 10	325	1465	687	4558	700	HD
9.5 - 36	122 A6	W 8	W 7	235	1360	646	4000	-	STD
12.4 - 36	126 A6	W 11	W 9 W 10	325	1465	696	4546	700	STD
12.4 - 36	139 A6	W 11	W 9 W 10	325	1465	696	4546	700	HD
8.3 - 36	107 A6	W 7	W 6	211	1295	628	4028	-	STD
13.6 - 36	125 A6	W 12	W 11	345	1515	713	4687	725	STD
8.3 - 36	113 A6	W 7	W 6	211	1295	628	4028	-	STD
13.6 - 36	129 A6	W 12	W 11	345	1515	712	4687	725	STD
12.4 - 36	135 A6	W 11	W 9 W 10	325	1465	696	4546	700	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
 R1  A6	 168 kg		Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

	SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
			REC RIM	ALT RIM						
										
NEW	12.4 - 36	139 A6	W 11	W 9 W 10	325	1465	696	4546	700	STD
	11.2 - 36	130 A6	W 10	W 9	290	1430			-	HD
Ø38"	13.6 - 38 (14.00 - 38)	139 A6	W 12	W 11	355	1565	735	4832	750	STD
	15.5 - 38	133 A6	W 14 L	-	395	1585	746	4660	-	STD
	15.5 - 38	138 A6	W 14 L	-	395	1585	746	4660	-	STD
	15.5 - 38	141 A6	W 14 L	-	395	1585	746	4660	-	STD
	18.4 - 38	153 A6	W 16 L	W 15 L	467	1750	794	5366	825	HD
	18.4 - 38	148 A6	W 16 L	W 15 L	467	1750	794	5366	825	HD
	20.8 - 38	166 A6	W 18 L	W 16 L	530	1835	846	5684	875	DB HD
	15.5 - 38	133 A6	W 14 L	-	395	1585	734	4748	-	HD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A6	168 kg	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
		REC RIM	ALT RIM						
									
16.9 - 38	143 A6	W 15 L	W 14 L	429	1685	788	4954	800	STD
20.8 - 38	156 A6	W 18 L	W 16 L	530	1835	846	5684	875	HD
15.5 - 38	133 A6	W 14 L	-	395	1585	746	4660	-	HD
11.2 - 38	117 A6	W 10	W 9	284	1460	686	4409	-	STD
13.6 - 38 (14.00 - 38)	131 A6	W 12	W 11	345	1565	735	4832	750	STD
20.8 - 38	148 A6	W 18 L	W 16 L	530	1835	846	5684	875	STD
13.6 - 38 (14.00 - 38)	142 A6	W 12	W 11	345	1565	735	4832	750	STD
16.9 - 38	141 A6	W 15 L	W 14 L	429	1685	788	4954	800	HD
14.00 - 38 (13.6 - 38)	131 A6	W 12	W 11	345	1565	735	4832	750	STD
20.8 - 38	166 A6	W 18 L	W 16 L	530	1835	846	5684	875	DB HD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A6	168 kg	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
		REC RIM	ALT RIM						
									
18.4 - 38	143 A6	W 16 L	W 15 L	467	1750	794	5366	825	HD
13.6 - 38 (14.00 - 38)	131 A6	W 12	W 11	345	1565	735	4832	750	HD
12.4 - 38	127 A6	W 11	W 9 W 10	325	1525	718	4670	-	STD
16.9 - 38	143 A6	W 15 L	W 14 L	429	1685	788	4954	800	HD
20.8 - 38	160 A6	W 18 L	W 16 L	530	1835	846	5684	875	STD
15.5 - 38	138 A6	W 14 L	-	395	1585	746	4760	-	HD
13.6 - 38 (14.00 - 38)	139 A6	W 12	W 11	345	1565	735	4832	750	HD
20.8 - 38	156 A6	W 18 L	W 16 L	530	1835	846	5684	875	STD
20.8 - 38	163 A6	W 18 L	W 16 L	530	1835	846	5684	875	DB HD
12.4 - 38	138 A6	W 11	W 9 W 10	325	1525	718	4670	-	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A6	168 kg	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
		REC RIM	ALT RIM						
									
14.00 - 38 (13.6 - 38)	139 A6	W 12	W 11	345	1565	735	4832	750	SPL
18.4 - 38	148 A6	W 16 L	W 15 L	467	1750	794	5366	825	HD
18.4 - 38	155 A6	W 16 L	W 15 L	467	1750	794	5366	825	STD
18.4 - 38	153 A6	W 16 L	W 15 L	467	1750	794	5366	825	STD
16.9 - 38	146 A6	W 15 L	W 14 L	429	1685	788	4954	800	STD
16.9 - 38	141 A6	W 15 L	W 14 L	429	1685	788	4954	800	STD
20.8 - 38	156 A6	W 18 L	W 16 L	530	1835	846	5684	875	STD
18.4 - 38	143 A6	W 16 L	W 15 L	467	1750	794	5366	825	STD
12.4 - 38	138 A6	W 11	W 9 W 10	325	1525	718	4670	-	STD
18.4 - 38	153 A6	W 16 L	W 15 L	467	1750	794	5366	825	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A6	168 kg	

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

	SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
			REC RIM	ALT RIM						
										
Ø42"	20.8 - 42	168 A6	W 18 L	W 16 L	535	1950	909	5733	-	DB HD
	20.8 - 42 (42)	158 A6	W 18 L	W 16 L	535	1950	909	5733	-	STD
	12.4 - 42	134 A6	W 10 W 10 A	-	322	1630	770	5011	-	STD
	20.8 - 42	158 A6	W 18 L	W 16 L	535	1950	909	5733	-	STD
	20.8 - 42	165 A6	W 18 L	W 16 L	535	1950	909	5733	-	STD
	9.5 - 42	125 A6	W 8	W 7	246	1510	721	4663	-	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A6		
	168 kg		
Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index			