


AGRIMAX RT 765

| | |
|---------------------|---|
| TIRE SIZE | 480/70 R 30 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | PULVERIZATOR / TRACTOR / MAȘINĂ DE RECOLTAT PODGORII / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 141 D |



DIMENSIUNI IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 479 | RIM REC | W 15 L |
| OD (MM) | 1478 | RIM ALT | W 14 L; W 16 L |
| SLR (MM) | 659 | ECE | E11-106R-005522 |
| RC (MM) | 4372 | SRI | 700 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 |
|------------|------|------|------|------|------|------|
| 65 | 1420 | 1650 | 1880 | 2115 | 2345 | 2575 |
| 50 | 1490 | 1735 | 1975 | 2220 | 2465 | 2705 |
| 40 | 1555 | 1805 | 2060 | 2315 | 2570 | 2820 |
| 30 | 1635 | 1900 | 2165 | 2435 | 2700 | 2965 |
| 10 LT | 1905 | 2215 | 2525 | 2835 | 3145 | 3455 |
| 10 HT | 1635 | 1900 | 2165 | 2435 | 2700 | 2965 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.