


AGRIMAX V-FLECTO

| | |
|--------------|--|
| TIRE SIZE | VF 650/60 R 38 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | HOCHLEISTUNGSTRAKTOR / TRACTOR |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 166 D |



ABMESSUNGEN IS STANDARD

| | | | |
|----------|------|---------|-----------------|
| SW (MM) | 650 | RIM REC | DW 23 B |
| OD (MM) | 1745 | RIM ALT | DW 21 B |
| SLR (MM) | 774 | ECE | E11-106R-005712 |
| RC (MM) | 5231 | SRI | 825 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 |
|--------------------------------|------|------|------|------|------|------|
| 70 | 2650 | 3080 | 3515 | 3950 | 4385 | 4820 |
| FROM 65 TO 40 | 2915 | 3390 | 3865 | 4345 | 4820 | 5300 |
| 30 | 2970 | 3455 | 3940 | 4430 | 4915 | 5405 |
| 20 | 3030 | 3525 | 4015 | 4515 | 5010 | 5510 |
| 10 | 3205 | 3725 | 4250 | 4775 | 5300 | 5830 |
| *UPTO 10 CYC WITH FRONT LOADER | 4080 | 4745 | 5410 | 6080 | 6745 | 7420 |
| 10HT | 2970 | 3455 | 3940 | 4430 | 4915 | 5405 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.