


MULTIMAX MP 529



TIRE SIZE	340/80 R 18
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	SOLLEVATORE TELESCOPICO
VERSIONE	STEEL BELTED
TIRE TYPE	TL
LI/SS	143 A8/B

DIMENSIONI US STANDARD

CODICE USA	94054305	RC (IN)	118.4
SW (IN)	13.5	RIM REC	11 ; 11 SDC ; W 11
OD (IN)	39.4	RIM ALT	W 10 ; 12 ; 12 SDC
SLR (IN)	17.5	ECE	E11-106R-002972

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	23	29	35	41	46	51	58	61	64
30	2890	3430	3910	4450	4990	5360	6010	-	-
25	2890	3430	3910	4450	4990	5360	6010	-	-
20	3100	3670	4190	4770	5350	5730	6440	-	-
15	3210	3800	4340	4940	5540	5940	6670	-	-
5 CYC.	3530	4330	5100	5860	6680	7260	8210	8660	9020
STATIC	5400	6640	7810	8990	10230	11130	12590	13270	13820

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.